

NOTICE INVITING QUOTATION

Ministry of Women & Child Development invite sealed quotations for renovation of Room no. 756, A Wing from amongst the reputed/experienced firms for various jobs (civil and electrical) as per the table below:

| S.No. | Description of items | Qty | | Unit | Rate | Amount |
|-------|---|-----|-----|------|------|--------|
| 1 | Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead. | | | | | |
| | For thickness of tiles 10 mm to 25 mm | 70 | sqm | sqm | | |
| 2 | Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead : | | | | | |
| | Of area 3 sq. metres and below | 6 | no. | each | | |
| 3 | Dismantling aluminium/ Gypsum partitions, doors, windows, fixed glazing and false ceiling including disposal of unserviceable surplus material and stacking of serviceable material with in 50 meters lead as directed by Engineer-in-charge. | 80 | sqm | sqm | | |
| 4 | Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level. | | | | | |
| | Cement mortar 1:3 (1 cement :3 coarse sand) | 18 | sqm | sqm | | |
| 5 | 12 mm cement plaster of mix : | | | | | |
| | 1:4 (1 cement: 4 fine sand) | 18 | sqm | sqm | | |
| 6 | 15 mm cement plaster on the rough side of single or half brick wall of mix : | | | | | |
| | 1:4 (1 cement: 4 fine sand) | 18 | sqm | sqm | | |
| 7 | Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete. | 100 | sqm | sqm | | |
| 8 | Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface : | | | | | |
| | Water thinnable cement primer. | 180 | sqm | sqm | | |
| 9 | Providing and applying white cement based putty of average thickness 1 mm, of approved | 180 | sqm | sqm | | |

Blj

| | | | | | | |
|----|---|------|-----|-----|--|--|
| | brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. | | | | | |
| 10 | Wall painting with acrylic emulsion paint of approved brand and manufacture to give an even shade: | | | | | |
| | Two or more coats on new work. | 250 | sqm | sqm | | |
| 11 | French spirit polishing : | | | | | |
| | Two or more coats on new works including a coat of wood filler. | 70 | sqm | sqm | | |
| 12 | Melamine polishing on wood work (one or more coat). | 70 | sqm | sqm | | |
| 13 | Providing and fixing specified wood frame work consisting of battens 50x25 mm fixed with rawl plug and drilling necessary holes for rawl plug etc. including priming coat complete. | | | | | |
| | Kiln seasoned and chemically treated hollock wood. | 1 | cum | cum | | |
| 14 | Providing and fixing plain lining with necessary screws/nuts & bolts/nails including a coat of approved primer on one face and fixed on wooden /steel frame work, complete as per direction of Engineer-in-charge. (Frame work shall be paid for separately) | | | | | |
| | 12mm thick commercial ply conforming to IS : 1328 BWR type. | 70 | sqm | sqm | | |
| 15 | Providing and fixing plywood 4 mm thick one side decorative veneer conforming to IS: 1328 (type-1) for plain lining / cladding with necessary screws, including priming coat on unexposed surface with: | | | | | |
| | Decorative veneer facings of approved manufacture. | 70 | sqm | sqm | | |
| 16 | Providing and fixing wooden moulded beading to door and window frames with iron screws, plugs and priming coat on unexposed surface etc. complete : | | | | | |
| | 2nd class teak wood | | | | | |
| | 50x12 mm | 30 | m | m | | |
| | 65x65 mm | 45 | m | m | | |
| | 20x20 mm | 45 | m | m | | |
| 17 | Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia. & length (hold fast lugs or dash fastener shall be paid for separately). | | | | | |
| | Second class teak wood | 0.30 | cum | cum | | |
| 18 | Providing and fixing ISI marked flush door shutters conforming to IS: 2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood | | | | | |

RBlegh

| | | | | | | |
|----|--|----|-----|------|--|--|
| | and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. | | | | | |
| | 35 mm thick including ISI marked Stainless Steel butt hinges with necessary screws. | 8 | sqm | sqm | | |
| 19 | Providing and fixing chromium plated brass 100 mm mortice latch and lock with 6 levers and a pair of lever handles of approved quality with necessary screws etc. complete. | 3 | no. | each | | |
| 20 | Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with IS : 3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701 mm to 1000 mm) with double speed adjustment with necessary accessories and screws etc. complete. | 3 | no. | each | | |
| 21 | Providing and fixing 150 mm bright finished floor brass door stopper with rubber cushion, necessary brass screws etc. to suit shutter thickness complete . | 3 | no. | each | | |
| 22 | Providing and fixing bright finished brass tower bolts (barrel type) with necessary screws etc. complete : 250x10 mm | 3 | no. | each | | |
| 23 | Providing and pasting graphic designer wall paper of approved make as per sample approved by the Client Department on existing wall including adhesive etc. all complete as per direction of Engineer-in-charge. | 65 | sqm | sqm | | |
| 24 | Providing and laying 14mm thick engineered hardwood wooden flooring of required size Marbau of PERGO/ or Pristine Noce Ross of MIKASA/ or Garden Walnut of KAHAR/ or equivalent make as per sample approved by the Engineer-in-charge, laid over 2mm thick foam & plastic sheet etc. all complete as per manufacturer's specifications. | 62 | sqm | sqm | | |
| 25 | Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37 mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5mm dia x 50 mm long with 6 mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the rate of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips | | | | | |

SB/raj

| | | | | | | |
|----|--|----|-----|-----|--|--|
| | of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound, jointing tapes, finishing with jointing compound in 3 layers covering upto 150 mm or both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with: | | | | | |
| | 12.5 mm thick tapered edge gypsum plain board conforming to IS: 2095- Part I. | 40 | sqm | sqm | | |
| 26 | Providing and Fixing 15 mm thick densified tegular edged eco friendly light weight calcium silicate false ceiling tiles of approved texture spintone/cosmos / Hexa or equivalent of size 595 x 595 mm in true horizontal level suspended on inter locking metal grid of hot dipped galvanised steel sections (galvanising @ 120 grams per sqm including both side) consisting of main "T" runner suitably spaced at joints to get required length and of size 24x38mm made from 0.33 mm thick (minimum) sheet, spaced 1200mm centre to centre, and cross "T" of size 24x28mm made out of 0.33mm (Minimum) sheet, 1200mm long spaced between main "T" at 600mm centre to centre to form a grid of 1200x600mm and secondary cross "T" of length 600mm and size 24x28mm made of 0.33mm thick (Minimum) sheet to be inter locked at middle of the 1200x 600mm panel to form grid of size 600x600mm, resting on periphery walls /partitions on a Perimeter wall angle pre-coated steel of size (24x24x3000 mm made of 0.40 mm thick (minimum) sheet with the help of rawl plugs at 450mm centre to centre with 25mm long dry wall screws @ 230mm interval and laying 15mm thick densified edges calcium silicate ceiling tiles of approved texture (Spintone / Cosmos/hexa) in the grid including, cutting/ making opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc. wherever required, Main "T" runners to be suspended from ceiling using G.I. slotted cleats of size 25x35x1.6mm fixed to ceiling with 12.5mm dia and 50mm long dash fasteners, 4mm G.I. adjustable rods with galvanised steel level clips | | | | | |

Blair